

FLEXPASS

LINEAR

A CALMING CHOICE. THE LINEAR COVER DESIGN PROVIDES A BASIC OPTION FOR SEAMLESS INTEGRATION WITH ANY SURROUNDING.



AVAILABLE IN: BLACK GREY WHITE BEIGE

INDALA PROVIDES A COMPLETE PRODUCT PORTFOLIO WITH THE FLEXSECUR™ TECHNOLOGY - THE CONFIDENCE OF SECURITY BETWEEN CARD AND READER. SUPPORTED WITH INNOVATIVE DESIGN AND RESPONSIVE CUSTOMER CARE.

LINEAR

FLEXPASS™

An ASSA ABLOY Group company

ASSA ABLOY

LINEAR

SPECIFICATIONS

Size Slim: 5.5" H x 1.7" W x 0.8" T (14.0cm x 4.3cm x 2.0cm)
 Wallswitch: 4.6" H x 3.0" W x 0.9" T (11.7cm x 7.6cm x 2.3cm)
 Classic: 2.3" H x 5.3" W x 0.8" T (5.8cm x 13.5cm x 2.0cm)

Read Range Slim: Up to 5" (12.7cm) using FlexCard™ standard card
 Wallswitch: Up to 5" (12.7cm) using FlexCard standard card
 Classic: Up to 5" (12.7cm) using FlexCard standard card

Input Voltage Slim: 4-16 VDC at reader
 Wallswitch: 4-16 VDC at reader
 Classic: 4-16 VDC at reader

Typical Current Draw
 Off Metal: Slim: 65 mA @ 12 V; 86 mA @ 5 VDC
 Wallswitch: 65 mA @ 12 V; 86 mA @ 5 VDC
 Classic: 65 mA @ 12 V; 86 mA @ 5 VDC

On Metal: Slim: 86 mA @ 12 V; 97 mA @ 5 VDC
 Wallswitch: 86 mA @ 12 V; 97 mA @ 5 VDC
 Classic: 86 mA @ 12 V; 97 mA @ 5 VDC

Maximum: Slim: 96 mA @ 12 V; 100 mA @ 5 VDC
 Wallswitch: 96 mA @ 12 V; 100 mA @ 5 VDC
 Classic: 96 mA @ 12 V; 100 mA @ 5 VDC

Operating Temperature -31° to +149°F (-35° to +65°C)
LED Indicator Tri-color standard (red, green, amber)
Audio Tone Standard, independently controllable (not tied to LED)
Output Formats Wiegand, ABA Track II Magnetic Stripe, and Serial TTL (requires use of BIL 232/422 Module)

Frequency 125 kHz (excitation)
Read Time (26-bit) 200 ms (from read to data output)
Security Various levels (configurable) FlexSecur™
Programming Factory or field programmable via FlexPass ProxSmith Programmer and Toolkit

Colors Black, Grey, White, Beige

Other Features Self Test, QuickFlash, WatchDog

Product Description	Package* Part #	Bezel Only Part #	CEM Only Part #
Slim, Black	FP4511A	FPZ-4511A	FPC-0500A
Slim, Grey	FP4515A	FPZ-4515A	FPC-0500A
Slim, White	FP4516A	FPZ-4516A	FPC-0500A
Slim, Beige	FP4517A	FPZ-4517A	FPC-0500A
Wallswitch, Black	FP4521A	FPZ-4521A	FPC-0500A
Wallswitch, Grey	FP4525A	FPZ-4525A	FPC-0500A
Wallswitch, White	FP4526A	FPZ-4526A	FPC-0500A
Wallswitch, Beige	FP4527A	FPZ-4527A	FPC-0500A
Classic, Black	FP4551A	FPZ-4551A	FPC-0500A
Classic, Grey	FP4555A	FPZ-4555A	FPC-0500A
Classic, White	FP4556A	FPZ-4556A	FPC-0500A
Classic, Beige	FP4557A	FPZ-4557A	FPC-0500A

*Packages include Core Electronics Module (CEM) and Bezel.



SLIM



WALLSWITCH



CLASSIC

Headquarters
 6850 B Santa Teresa Blvd.
 San Jose, California 95119-1205 USA
 Toll Free: 800-779-8663 (USA only)
 Tech. Support: 800-646-3252 (USA only)
 Phone: +1 408 361 4700
 Fax: +1 408 361 4701

European Office
 Wokingham, Berkshire UK
 Phone: + 44 (0) 1189 121 780
 Fax: +44 (0) 1189 121 790

Asia Pacific Office
 Hong Kong
 Phone: +852 2587 6008
 Fax: +852 8343 7688

Mexico Office
 León, Gto. México
 Phone: +52 477 779 7784
 Fax: +52 477 779 1493

Brazil Office
 São Paulo, Brazil
 Phone: +55 11 5576 6660
 Fax: +55 11 5576 6661

Latin America Office
 Buenos Aires, Argentina
 Phone: +54 11 4857 1767
 Fax : +54 11 4857 3573




FlexISO



FlexKey



FlexCard



FlexISO XT

APPROVALS
 UL 294/cUL, FCC Certification - United States, Canada Certification, CE Mark - Europe, Australia C-Tick, New Zealand/EMC

WARRANTY
 Indala warrants this product against defects in material and workmanship under normal use and service. The warranty period commences with the date of shipment. See complete warranty statement for further details.

Read range stated when readers installed according to instructions. Read range may vary when mounted on metal and with different cover designs. Illumination colors may differ based on cover design color. Specifications subject to change without notice. Indala reserves the right to discontinue any product without notice.

Indala and FlexPass are registered trademarks of Indala, an ASSA ABLOY Group company.
 All other products or service names are the property of their respective trademark owners.
 © 2003 Indala. All rights reserved. Printed in the U.S.A.
 lineards 10-2003



Credentials
 The Indala FlexPass Linear is designed to work seamlessly with Indala FlexPass credentials such as the FlexISO™, FlexKey™, FlexCard, and FlexISO XT Durable Composite Card.